Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 08/31/2017

SECTION 1: Identification	
1.1. Identification	
Product form	: Mixture
Product name	: BR-CWDA, CAR WASH DRYING AGENT
Product code	BR-CWDA5, BR-CWDA55
1.2. Recommended use and restriction	
No additional information available	
1.3. Supplier	
BROTHERS RESEARCH CORPORATION	
2245 Air Park Drive	
Burlington, NC 27215	
T 800-638-7245	
1.4. Emergency telephone number	
Emergency number	: 800-424-9300
SECTION 2: Hazard(s) identification	
SECTION 2: Hazard(s) identification 2.1. Classification of the substance or p	
GHS-US classification Flammable liquids H227	Combustible liquid
Category 4	
Carcinogenicity Category H350 1B	May cause cancer (Dermal, Inhalation, oral)
Full text of H statements : see section 16	
2.2. GHS Label elements, including pre	cautionary statements
GHS-US labeling Hazard pictograms (GHS-US)	
nazaru pictograms (GHS-OS)	
Signal word (CLIC LIC)	
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H227 - Combustible liquid H350 - May cause cancer (Dermal, Inhalation, oral)
Precautionary statements (GHS-US)	: P201 - Obtain special instructions before use
,	P202 - Do not handle until all safety precautions have been read and understood
	P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking P280 - Wear eye protection, face shield, protective clothing, protective gloves
	P308+P313 - If exposed or concerned: Get medical advice/attention
	P370+P378 - In case of fire: Use extinguishing powder, foam, carbon dioxide (CO2) to
	extinguish
	P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up
	P501 - Dispose of contents/container to an approved waste disposal plant, an authorized waste
	collection point
2.3. Other hazards which do not result	in classification
No additional information available	
2.4. Unknown acute toxicity (GHS US)	
Not applicable	
SECTION 3: Composition/Information	on on ingredients
3.1. Substances	
Not applicable 3.2. Mixtures	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
DICOCODIMONIUM CHLORIDE	(CAS No) 61789-77-3	6 - 10	Not classified
Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).]	(CAS No) 64742-46-7	6 - 9	Carc. 1B, H350
butyl glycolether	(CAS No) 111-76-2	1-3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures		
4.1. Description of first aid measures		
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow victim to breathe fresh air. Allow the victim to rest.	
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.	
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist. Rinse eyes with water as a precaution.	
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.	
4.2. Most important symptoms and effect	s (acute and delayed)	
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.	
Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.	
4.3. Immediate medical attention and spe	cial treatment, if necessary	
Treat symptomatically.		
SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishi	ng media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.	
Unsuitable extinguishing media	: Do not use a heavy water stream.	
5.2. Specific hazards arising from the che	emical	
Fire hazard	: Combustible liquid. Highly flammable liquid and vapor.	
Explosion hazard	: May form flammable/explosive vapor-air mixture.	
Reactivity	: Highly flammable liquid and vapor.	
5.3. Special protective equipment and protective	ecautions for fire-fighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	
SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Evacuate unnecessary personnel.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Ventilate area.		
6.2. Environmental precautions			
Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Notify authorities if product enters sewers or public waters.			
6.3. Methods and material for containme	nt and cleaning up		
Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.		
Other information	: Dispose of materials or solid residues at an authorized site.		
6.4. Reference to other sections			
See Heading 8. Exposure controls and personal p	protection. For further information refer to section 13.		
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.		
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 		
7.2 Conditions for sofe stores includin			
7.2. Conditions for safe storage, includin			
Technical measures	 Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Does not require any specific or particular technical measures equipment. 		
Storage conditions	: Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Store in a well-ventilated place. Keep cool.		
	Store locked up.		

Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

outyl glycolether (1 CGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
	CHLORIDE (61789-77-3)	·
NE 2 11 11		
Not applicable		
Distillates (petroleu petroleum fraction v	vith hydrogen in the presence of a catalyst. It	, [A complex combination of hydrocarbons obtained by treating a consists of hydrocarbons having carbon numbers predominantly in mately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7)

Appropriate engineering controls

: Ensure good ventilation of the work station.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls

: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask. Wear respiratory protection

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical p	properties
9.1. Information on basic physical and c	hemical properties
Physical state	: Liquid
Appearance	: Orange Liquid.
Color	: Orange
Odor	: Sweet
Odor threshold	: No data available
рН	: 5
Melting point	: ≈ °F No Data
Freezing point	: No data available
Boiling point	: 370 - 550 °F
Flash point	: >= 212 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: < 1 mm Hg
Relative vapor density at 20 °C	: No data available
Relative density	: 0.9 @ 60.0 F
Solubility	: Water: < 0.01
Log Pow	: No data available
Auto-ignition temperature	: 420 °F
Decomposition temperature	: No data available
Viscosity	: >= 80 cP
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Highly flammable liquid and vapor.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Open flame. Overheating. Heat. Sparks. Direct sunlight. Extremely high or low temperatures. Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products May release flammable gases, fume, Carbon monoxide, Carbon dioxide

May release naminable gases. Turne. Carbon monoxide. Carbon dioxide.	
SECTION 11: Toxicological information	

11.1. Information on toxicological effects	
Acute toxicity	: Not classified
butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
ATE US (oral)	1746 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	450 ppmV/4h
ATE US (vapors)	2.2 mg/l/4h
ATE US (dust, mist)	2.2 mg/l/4h
Skin corrosion/irritation	: Not classified
	pH: 5
Serious eye damage/irritation	: Not classified
	pH: 5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: May cause cancer (Dermal, Inhalation, oral).
butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
	Based on available data, the classification criteria are not met
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.

SECTIC	ON 12: Ecological information	
12.1.	Toxicity	
Ecology -	general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
LC50 fish 1	1474 ppm (96 h; Oncorhynchus mykiss)
EC50 Daphnia 1	1550 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	911 mg/l (72 h; Pseudokirchneriella subcapitata)
Threshold limit algae 2	88 mg/l (72 h; Pseudokirchneriella subcapitata)

Persistence and degradability	Not established.
butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.
DICOCODIMONIUM CHLORIDE (61789-77-3)
Persistence and degradability	Not established.
petroleum fraction with hydrogen in the pre	e, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a esence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7)
Persistence and degradability	Not established.
2.3. Bioaccumulative potential	
BR-CWDA, CAR WASH DRYING AGENT	
Bioaccumulative potential	Not established.
butyl glycolether (111-76-2)	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
DICOCODIMONIUM CHLORIDE (61789-77-3]
Bioaccumulative potential Distillates (petroleum), hydrotreated middle	Not established.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre- the range of C11 through C25 and boiling in Bioaccumulative potential	Not established.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 2.4. Mobility in soil	Not established. e, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a essence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in n the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7)
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 12.4. Mobility in soil butyl glycolether (111-76-2)	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 12.4. Mobility in soil	Not established. e, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a essence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in n the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7)
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 12.4. Mobility in soil butyl glycolether (111-76-2) Surface tension	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 12.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 12.5. Other adverse effects	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003)
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre- the range of C11 through C25 and boiling in Bioaccumulative potential 12.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 12.5. Other adverse effects Effect on the global warming	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003) : No known effects from this product.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the preter the range of C11 through C25 and boiling in Bioaccumulative potential 2.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 2.5. Other adverse effects Effect on the global warming	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003)
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 12.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 12.5. Other adverse effects	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003) : No known effects from this product.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 2.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 2.5. Other adverse effects Effect on the global warming GWPmix comment	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003) : No known effects from this product. : No known effects from this product. : Avoid release to the environment.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pre the range of C11 through C25 and boiling in Bioaccumulative potential 2.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 2.5. Other adverse effects Effect on the global warming GWPmix comment Dther information SECTION 13: Disposal consideratio	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003) : No known effects from this product. : No known effects from this product. : Avoid release to the environment.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pretthe range of C11 through C25 and boiling in Bioaccumulative potential 2.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 2.5. Other adverse effects Effect on the global warming GWPmix comment Dther information SECTION 13: Disposal consideration	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a sence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003) : No known effects from this product. : No known effects from this product. : Avoid release to the environment.
Bioaccumulative potential Distillates (petroleum), hydrotreated middle petroleum fraction with hydrogen in the pretthe range of C11 through C25 and boiling in Bioaccumulative potential 2.4. Mobility in soil butyl glycolether (111-76-2) Surface tension 2.5. Other adverse effects Effect on the global warming GWPmix comment Dther information SECTION 13: Disposal consideratio 3.1. Disposal methods	Not established. a, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a esence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7) Not established. 0.065 N/m (20 °C; 003) : No known effects from this product. : Dispose of contents/container to Dispose in a safe manner in accordance with local/national

Department of Transportation (DOT) In accordance with DOT

Other information

: No supplementary information available.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG

Transport by sea

UN-No.(IATA)

Transport document description (IMDG)	: UN TO BE COMPLETED/CALCULATED
UN-No. (IMDG)	: TO BE COMPLETED/CALCULATED
Air transport	
Transport document description (IATA)	: UN TO BE COMPLETED/CALCULATED

: ----- TO BE COMPLETED/CALCULATED ------

SECTION 15: Regulatory information

15.1. US Federal regulations

BR-CWDA, CAR WASH DRYING AGENT

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

DICOCODIMONIUM CHLORIDE (61789-77-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] **(64742-46-7)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information	
Data sources	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full	Full text of H-phrases:		
	H227	Combustible liquid	
	H302	Harmful if swallowed	
	H312	Harmful in contact with skin	
	H315	Causes skin irritation	
	H319	Causes serious eye irritation	
	H332	Harmful if inhaled	
	H350	May cause cancer	

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product